



# PRATLEY®

## General

Pratley Gasket Maker is a high quality silicone based sealing compound which cures at room temperature forming a tough elastic rubber seal.

## Properties

- Tough and elastic silicone rubber for superior sealing.
- Temperature resistant from -50°C to +300°C for short periods.
- Chemically resistant to: Petrol, Diesel, Paraffin, Water, Oil, Anti-Freeze. Not for use on parts continuously immersed in petrol.
- Non-corrosive.
- No negative impact on electrical components (eg. vehicle sensors).

## Application

**Step 1:** Surfaces to be sealed must be cleaned and degreased. A reputable cleaner such as “Pratley Safety Cleaner” is recommended.

**Step 2:** Apply Pratley Gasket Maker in one continuous bead to only one of the sealing surfaces. Ensure all bolt holes are encircled.  
Note: To ensure a proper seal, do not apply Pratley Gasket Maker to both sealing surfaces. Also, ensure that the applied bead is continuous with no air gaps separating the bead.

**Step 3:** Assemble the sealing surfaces and tighten the bolts as soon as possible (Pratley Gasket Maker will begin to skin within 40 minutes)

**Step 4:** Allow 24 hours for full cure.

**Step 5:** Replace the cap after use.

### NON-HAZARDOUS

If medical advice is needed, have product container or label at hand. Keep out of reach of children. Read label before use.


### Clean



### Apply



### Assemble



61001540780494

90 ml

[www.pratleyadhesives.com](http://www.pratleyadhesives.com)



PRATLEY (PTY) LTD P O Box 3055 • Kenmare 1745 Gauteng • South Africa  
Tel.:+27 11 955-2190 • Fax:+27 11 955-3918 • email: [sales@pratley.co.za](mailto:sales@pratley.co.za)