

PRATLEY®

Flexiseal

PROPERTIES

PRATLEY FLEXISEAL is a top quality permanently flexible sealant with good adhesive properties: • Accepts paint very well • After curing it is waterproof and resists most chemicals • Weather and ultra violet resistant.

SUGGESTED USES: • Ideal for filling large wall cracks • Seal corrugated iron roof sheets and roof bolt heads • Use as a pipe thread sealant • Fill nail holes • Seal around bath and basin • Seal around toilet bowl inlet pipe • Seal around window and door frames • Seal and join leaking gutters.

N.B.: 1) Not recommended for use on Perspex or Plastic Tiles. 2) Prolonged immersion in water will soften FLEXISEAL.

DIRECTIONS FOR USE:

1. Ensure that the surfaces are clean and free from oil and soap. Absorbent surfaces such as concrete, brick and plaster should be lightly dampened before application.
2. Cut nozzle to suit size of bead required.
3. Dispense by using a cartridge gun.
4. Excess FLEXISEAL should be cleaned off with damp cloth immediately.
5. Once set (after 72 hours or much longer for large volumes) FLEXISEAL may be painted over. **It is essential that FLEXISEAL be fully cured before painting.**

CAUTION: FLEXISEAL is very mild indeed. However, washing the hands after working with it is good practice. It is manufactured to stringent specifications but since it is used under conditions outside our control, we cannot accept liability for any possible failures.

Pratley (Pty) Ltd. (1996/003890/07)
PO Box 3055 • Kenmare 1745
Gauteng • South Africa
www.pratley.com

EIENSKAPPE:

PRATLEY FLEXISEAL is 'n hoë gehalte permanent-buigsame verseëllaar met goeie kleef eienskappe:
• Geskik om oor te verf • Na stolling is dit waterdig en bestand teen die meeste chemikalieë • Weer en ultra violet bestand.

VOORGESTELDE GEBRUIKE: • Uiters geskik vir die opvol van groot muurkruke • Verseël golfyster dakplate en dakboutkoppe • Gebruik as afdigmiddel vir pyp-skroefdraad • Vul spykergate • Verseël om bad en wasbak • Verseël om inlaatpyp van toiletbak • Verseël om venster- en deurrame • Verseël en las geute wat lek.

L.W.: 1) Word nie aanbeveel vir gebruik op Perspex of Plastiekteëls. 2) Langdurige indompeling in water sal FLEXISEAL sag maak.

GEBRUIKSAANWYSINGS:

1. Maak seker dat oppervlakte skoon en olie- en seepvry is. Absorberende oppervlakte soos beton, baksteen en pleisterwerk moet voor aanwending klam gemaak word.
2. Sny tuit vir die benodigde grootte.
3. Wend aan deur buis in 'n aanwender te plaas.
4. Oortollige FLEXISEAL behoort onmiddellik met 'n klam lap afgevee te word.
5. Na stolling (binne 72 uur of baie langer vir groot volumes), kan daar oor FLEXISEAL gevef word. **Dit is noodsaaklik om FLEXISEAL deeglik te laat droog word voordat oor dit gevef word.**

WAARSKUWING: FLEXISEAL werk sag op die hande. Dit is eger goed om die hande na gebruik daarvan te was. Dit word volgens streng spesifikasies vervaardig, maar aangesien ons geen beheer oor gebruiksomstandighede het nie, aanvaar ons geen verantwoordelikheid as dit sou misluk nie.